



# DELTA-XERO

THE FUTURE IS SYSTEM RELIABILITY

## DX0-1525 Cartridge

The modern, eco-friendly solution to fluid conditioning.

- Particle filtration down to **0.1 μ**
- Designed for mineral and synthetic fluids
- Hydraulic, lube and gear applications
- Smart & effective maintenance system
- Operation and maintenance cost reduction
- Extend equipment lifetime
- Minimised fluid oxidation
- Mitigation and reduction of **varnish**
- Increased production uptime
- Reduced fluid changes
- Eco-friendly
- Easy to service
- Small footprint
- **100% Recycled** media



Maintaining healthy fluid by removing:

- **Bacteria**
- **Water (free and emulsified)**
- **Oxidation products (Sludge and resin)**

### Technical Specifications

Part No.	DX0-1525
Weight ( Dry )	1.15 kg
Weight ( Saturated )	Up to 1.4ltrs
Flow capacity	0.5 lpm @32 cSt
Water absorption, free & bound	Up 0.85Ltrs
Min and max limits	Min 0°C - Max 100°C
Material	PP Cellulose mix
Package dimensions	152 mm x 152 mm x 230 mm



© 2021 Delta-Xero All Rights Reserved. All information contained in this publication is indicative only and may be subject to change without prior notice.



Authorised Distributor



t: +44 1264 860 186  
e: spares@simplexturbulo.com

Simplex-Turbulo is part of the **SLX** GROUP



Delta-Xero Distribution Ltd  
Unit 5, Pennant Park, Standard Way,  
Fareham, Hampshire,  
PO16 8XU  
t: +44 2392 874 755  
e: sales@delta-xero.com