



## DXO Cartridge

The modern, eco-friendly solution to fluid conditioning.

- Particle filtration down to **0.1  $\mu$**
- Designed for mineral and synthetic fluids
- Hydraulic, lube and gear applications
- Smart & effective maintenance system
- Operation and maintenance cost reduction
- Extend equipment lifetime
- Minimised fluid oxidation
- Mitigation and reduction of **varnish**
- Increased production uptime
- Reduced fluid changes
- Eco-friendly
- Easy to service
- Small footprint
- **100% Recycled** media



Maintaining healthy fluid by removing:


- **Bacteria**
- **Water (free and emulsified)**
- **Oxidation products (Sludge and resin)**

### Technical Specifications

|                                |                          |
|--------------------------------|--------------------------|
| Part No.                       | DXO                      |
| Weight ( Dry )                 | 1.85 kg                  |
| Weight ( Saturated )           | Up to 4.5 kg             |
| Flow capacity                  | 1 lpm @32 cSt            |
| Water absorption, free & bound | Up to 2600 ml            |
| Min and max limits             | Min 0°C - Max 100°C      |
| Material                       | PP Cellulose mix         |
| Package dimensions             | 192 mm x 192 mm x 265 mm |



© 2022 Delta-Xero All Rights Reserved. All information contained in this publication is indicative only and may be subject to change without prior notice.



Authorised Distributor



t: +44 1264 860 186  
e: spares@simplexturbulo.com

Simplex-Turbulo is part of the **SLX** GROUP